



WEICON Solutions for

Energy Technology



www.weicon.com/app

www.weicon.com

V 1.18

For further packing sizes and more detailed product information, please visit our website www.welcon.com



Elastic Adhesives and Sealants

Elastic adhesives and sealants are used in many areas of industrial production and assembly.

They combine the advantages of the adhesive and sealant technology and are used wherever the elasticity and sealing effect of a joint are exposed to high stresses.



Gearbox cover seal with Black-Seal

Flex 310 M® Stainless Steel

- non-corrosive
- stainless steel look

310 ml
 13656310



Flex 310 M® Liquid

- casting and coating mass
- self-levelling
- ISEGA certified

310 ml
 13333310
 white



Flex 310 M® 2 K

- fast-curing
- resistant to UV rays
- for stainless steel, aluminium and non-ferrous metals

250 ml Special Mixing Nozzle
 13305250 13309997
 grey

Black-Seal

- high resistance to oil, grease and chemicals
- high temperature resistance from -50°C (-58°F) to +280°C (+536°F)

200 ml 13051200
 Press pack
 310 ml 13051310
 Cartridge



WEICON Solutions for Energy Technology

Technical Sprays and Technical Liquids

Technical sprays and liquid substances are used in almost all areas of industry.

They maintain and protect surfaces when cleaning, degreasing, dissolving and separating and are an indispensable part of everyday work.



Degreasing with Cleaner Spray S

Cleaner Spray S

- powerful
- evaporates without residue
- non-greasy

500 ml ✓ 5 L ✓
11202500 15200005

Surface Cleaner

- for pre-treatment of adhesive surfaces
- residue-free and quick evaporation
- for metals and plastics

150 ml ✓ 400 ml ✓
11207150 11207400

5 L ✓
15207005

Sealant and Adhesive Remover

- removes sealing and cured adhesive residues
- for removal of old paint and varnish

400 ml ✓ 5 L ✓
11202400 15213005

Citrus Cleaner

- universal cleaner based on citrus peel extracts
- cleans machines and systems, precision engineering components and precision mechanisms

400 ml ✓ 5 L ✓
11217400 15210005



Electro Contact Cleaner

- increases electrical conductivity
- reduces the loss of voltage

400 ml ✓ 5 L ✓
11210400 15212005

Contact Spray

- for the protection and care of electrical contacts and components
- keeps contacts, fuses, cable connections, etc. free from oxidation

400 ml ✓
11152400

W 44 T® Multi-Spray

- lubricates precision mechanics
- repels moisture
- protects against corrosion

400 ml ✓ 500 ml ✓
11251400 11251550

5 L ✓
15251005



Rust Protection 2000 PLUS

- high corrosion and weathering resistance

400 ml ✓ 400 ml ✓
11012400 11013400
charcoal-grey silver grey

Zinc Spray



- cathodic corrosion protection
- can be painted over
- > 1.050 hours salt spray test

400 ml ✓
11000400



For further packing sizes and more detailed product information, please visit our website www.weicon.com



Plastic Metal

WEICON Plastic Metal is ideal for providing fast, cost-effective and durable repairs and coatings for many different types of material.



WEICON CBC Chocking Backing Compound

Special epoxy resin system for the shimming and backfilling of systems difficult to align.

- liquid and self-levelling
- vibration-resistant
- impact- and break-resistant

3,0 kg (2,0 l) ✓ 10,0 kg (6,6 l) ✓
10110030 10110110



European Exhibition Award for creativity and innovation

WEICON SF

- pasty, steel-filled
- for fast repairs (5 minute pot life)
- certified by DNV-GL



0,5 kg ✓ 2,0 kg ✓
10250005 10250020

WEICON HB 300

- steel-filled
- pasty, for spatula application
- high-temperature-resistant



-35°C (-31°F) to +280°C (+536°F)

1,0 kg ✓
10450010

Repair Sticks

The simple solution for all repair and maintenance works. Easy to use. Ready to use, can be easily cut into small amounts for minor repairs at any time.



Plastic



Certified to NSF/ANSI 61


- pasty
- colour light blue
- NSF approval for drinking water ANSI Standard 61

115 g ✓
10536115

Titanium

- high temperature resistance (-50°C to +300°C)
- colour grey-green
- pasty, for spatula application

115 g ✓
10535115





WEICON Solutions for Energy Technology

Epoxy Adhesives

WEICON Epoxy Adhesives are cold-curing, solvent-free two-component systems with extremely strong adhesion. They allow material bonds with high traction and impact resistance and are therefore perfect for assembly, repair and production.

Easy-Mix HT 180

- high-temperature-resistant
- steady
- shock- and impact-resistant



-50°C (-58°F) to
+180°C briefly up to
+230°C (+446°F)

50 ml

10650850



Easy-Mix S 50

- ideal for serial production with short cycle times
- fast-curing (pot life 4-5 minutes)

50 ml

10650050

Quadro Mixing Nozzle



suitable for RK-7000 and Easy-Mix S 50

10650005

Helix Mixing Nozzle



suitable for Easy-Mix HT 180

10650006

Easy-Mix RK-7000

WEICON Easy-Mix RK-7000 bonds lots of materials, such as plastics, metals or ceramic with strong traction as well as high shearing and peeling resistance.

Easy-Mix RK-7000 can be used universally. Possible areas of application are synthetic technology, metalwork, car body and vehicle construction, mechanical engineering, electro-technology, wood processing or trade fair and exhibition building.

- highly viscous, high strength, impact-resistant, residual elasticity
- pot life: approx. 15 minutes
- temperature-resistant from -55°C to +125°C



Easy-Mix Hand Dispenser D 50

10653050

50 ml

10650500



For further packing sizes and more detailed product information, please visit our website www.weicon.com



WEICONLOCK® - Anaerobic Adhesives and Sealants

Specially made for economical threadlocking, retaining and sealing of threaded, cylindrical and pipe assemblies.

After curing, the product forms an adhesive bond resistant to vibration and impact as well as chemicals, solvents and temperatures of -60°C up to +150°C.



Sealing shut-off valves with AN 305-77

AN 302-43



- threadlocking
- thread connections up to M 36
- drinking water and DVGW approval

higher viscosity
medium strength
disassembly with normal tools

50 ml 200 ml
30243150 30243200



AN 302-70



- locking of threads and stud bolts
- thread connections up to M 36
- drinking water and DVGW approval

medium viscosity
high strength
hard to disassemble

50 ml 200 ml
30270150 30270200



AN 305-11



- sealing of threaded pipes and fittings
- drinking water and DVGW approval

high viscosity
medium strength
disassembly with normal tools

50 ml 200 ml 300 ml
30511150 30511200 30511300



AN 305-77



- sealing of threaded pipes and fittings
- drinking water and DVGW approval

high viscosity
medium strength
disassembly with normal tools

50 ml 200 ml 300 ml
30577150 30577200 30577300



AN 306-30

- bearing and stud bolt adhesive
- up to a gap of 0.2 mm

high viscosity
high strength
hard to disassemble

50 ml 200 ml
30630150 30630200



AN 306-60

- bearing and stud bolt adhesive
- for worn bearing rings and bushings with a gap of up to 0.5 mm

high viscosity
high strength
hard to disassemble

50 ml 200 ml 300 ml
30660150 30660200 30660300



BAM tested and safety-related evaluated according to leaflet M 034-1
List of nonmetallic materials supporting document to code of practice M 034e "Oxygen" (DGVU Information 213-074)

BAM tested and safety-related evaluated according to leaflet M 034-1
List of nonmetallic materials supporting document to code of practice M 034e "Oxygen" (DGVU Information 213-074)



WEICON Solutions for Energy Technology


Contact Cyanoacrylate Adhesive

WEICON Contact is a solvent-free instant adhesive. It bonds various materials, such as metal, glass, wood, plastic, ceramic, leather and rubber in seconds.

VA 250 Black

- black, rubber-filled
- high peeling and impact resistance
- temperature-resistant from -50°C to +135°C

30 g ✓	60 g ✓	500 g ✓
12600030	12600060	12600500



Attaching rubber profiles

Plast-o-Seal® - Permanently Plastic Universal Sealant



Plast-o-Seal®

- permanent plastic universal sealant, non-curing
- no evaporation of solvents
- immediate assembly possible

90 g ✓	120 g ✓	230 g ✓	300 g ✓
30000090	30000120	30000230	30000300
Tube	Brush top can	Press pack	Cartridge

For further packing sizes and more detailed product information, please visit our website www.welcon.com



Anti-Seize - Assembly Pastes/Sprays

All kinds of influencing factors, e.g. moisture, temperature or friction, repeatedly lead to corrosion damage, seizure and wear on machines and installations.

Extensive repair and maintenance work at considerable costs are the consequence.

Especially under extreme conditions of application, e.g.

- high operation temperatures
- high pressure loads
- outdoor weather conditions

such consequences frequently occur.



Anti-Seize High-Tech



- metal-free, NSF approval
- high-temperature-resistant up to +1400°C (+2552°F)

120 g ✓ 26100012	400 g ✓ 26100040	400 ml ✓ 27050400
Brush top can	Cartridge	Spray
450 g ✓ 26100045	500 g ✓ 26100050	10 kg ✓ 26100910
Can	Brush top can	Bucket

Anti-Seize Nickel

- for extreme conditions
- can be applied at a large temperature range between -30°C to +1450°C

120 g ✓ 26050012	400 g ✓ 26050040	450 g ✓ 26050045
Brush top can	Cartridge	Can
500 g ✓ 26050050	10 kg ✓ 26050910	
Brush top can	Bucket	





WEICON Solutions for Energy Technology

Allround Lubricant

Even in the present „high-tech age“ problems due to friction and wear are still an issue in a lot of industrial sectors. Extensive repairs, longer downtimes, and shorter maintenance intervals and service lives of plants and machines are the consequence and cause enormous costs every year.

Therefore, it is important to already meet the requirements for long-term operational reliability of plants and equipment during the development and construction phase.



AL-W

- extremely water-repellent
- high lubrication
- temperature-resistant from -25°C to +80°C

400 g ✓

26450040

Cartridge

1,0 kg ✓

26450100

Can

AL-M

- strong adhesion
- high pressure resistant
- with MoS₂

400 g ✓

26400040

Cartridge

1,0 kg ✓

26400100

Can



Thread Sealing Cord DF 175

WEICON DF 175 is a patented thread sealing cord made of 100% PTFE. It permanently and securely seals almost all metal and plastic threads. WEICON DF 175 reliably compensates the space on threads and forms a PTFE film in the required thickness when connecting screws.

- Immediate sealing, temperature range -200°C to +240°C (-328 to +464°F)
- drinking water approvals according to NSF, WRAS
- 100% PTFE solid, silicone-free

175 m dispenser

30010175



TZW

BAM



BAM tested and safety-related evaluated according to leaflet M 034-1
List of nonmetallic materials supporting document to code of practice M 034e "Oxygen" (DGV Information 213-074)

For further packing sizes and more detailed product information, please visit our website www.weicon.com




Special Tools

For a number of unusual applications, we offer a range of special tools, which special tools which meet these requirements. Whether for the dismantling of large cable diameters or for working on high voltage cables, WEICON TOOLS has the solution!

Dismantling Tool No. 25

- for convenient longitudinal and circular cuts
- safe work thanks to the concealed blade
- conductor protection thanks to the curved blade tip
- easy working, even at low temperatures
- precise, durable and replaceable turnover blade

mm	g	Art.-No.
210	163	52000025



Tools Set

With our tool sets, we offer solutions for almost all industries and the most different applications.

Crimp-Set Pro

Allround equipment for crimping with wire end ferrules

- Duo-Crimp No. 300
- Wire Stripper No. 7 Magic
- high quality shaker with 400 wire ends (0.5 - 2.5 mm²) according to DIN 46228

mm	g	Art.-No.
Length x Width x Height		
340 x 280 x 55	950	52880002



Starter-Set Pro

Ideal selection for house installation

- Wire Stripper No. 5
- Coax-Stripper No. 2
- Cable Stripper No. S 4-28
- Round Cable Stripper No. 13

mm	g	Art.-No.
Length x Width x Height		
255 x 210 x 60	575	52880001



Wire End Ferrules Assortment Box (DIN 46228)

Cross Section	Content	Colour
0,50 mm ²	50	white
0,75 mm ²	100	grey
1,00 mm ²	100	red
1,50 mm ²	100	black
2,50 mm ²	50	blue





WEICON Solutions for

Energy Technology

Tools for the Solar Industry

Solar-Flex

- very high initial bonding power
- free of silicone, isocyanate, halogens and solvents
- temperature-resistant from -40°C to +90°C (-40°F to 194°F)

290 ml 13750290
white

290 ml 13752290
grey



Mini-Solar No. 3

- quick stripping of all common solar cables with outer diameters from 1.5 mm² to 6 mm²
- precise work with adjustable length stop (6 - 28 mm)
- integrated, well-accessible side cutter up to 4 mm²

mm	g	mm ²	Ømm	Art.-No.
125	58	1,5 - 6 (15 - 9 AWG)	-	52002003



Special tools for dismantling and stripping all common cables in the solar sector



Wire Stripper No. 7 Solar

- automatic Wire Stripper
- precise work with optical length scale (up to 26 mm)
- integrated, well-accessible side cutter up to 3 mm Ø

mm	g	mm ²	Art.-No.
170	218	Solar cable 1,5 - 6 (15 - 9 AWG)	51002007



**WEICON GmbH & Co. KG
(Headquarters)**

Königsberger Str. 255 · DE-48157 Münster
P.O. Box 84 60 · DE-48045 Münster
Germany
phone +49 (0) 251 9322 0
info@weicon.de

WEICON Middle East L.L.C.

Jebel Ali Ind Area 1
P.O. Box 118 216 · Dubai
United Arab Emirates
phone +971 4 880 25 05
info@weicon.ae

WEICON Inc.

20 Steckle Place · Unit 20
Kitchener · Ontario N2E 2C3 · Canada
phone +1 877 620 8889
info@weicon.ca

WEICON Kimya Sanayi Tic. Ltd. Şti.

Orhan Gazi Mahallesi 16. Yol Sokak No: 6
34517 Hadimköy-Esenyurt · Istanbul
Turkey
phone +90 (0) 212 465 33 65
info@weicon.com.tr

WEICON Romania SRL

Orhan Gazi Mahallesi 16. Yol Sokak No: 6
Str. Podului Nr. 1
547176 Budiu Mic (Targu Mures) · Romania
phone +40 (0) 3 65 730 763
office@weicon.com

WEICON SA (Pty) Ltd

Unit No. D1 · Enterprise Village
Capricorn Drive · Capricorn Park
Muizenberg 7945 (Cape Town) · South Africa
phone +27 (0) 21 709 0088
info@weicon.co.za

WEICON South East Asia Pte Ltd

7 Soon Lee Street
#01-11 ISPACE · Singapore 627608
Phone (+65) 6710 7671
info@weicon.com.sg

WEICON Czech Republic s.r.o.

Teplická 305
CZ-417 61 Teplice-Bystřany
Česká republika
phone +42 (0) 417 533 013
info@weiconcz.cz

WEICON Ibérica S.L.

Av. de Somosierra 18, Nave 6
San Sebastián de los Reyes
28703 Madrid · Spain
phone +34 (0) 914 7997 34
info@weicon.es

WEICON Italia S.r.L.

Via Capitano del Popolo, 20
16156 Genova · Italy
phone +39 (0) 329 235 9592
info@weicon.it

www.weicon.com



Management System
ISO 9001:2015
ISO 14001:2015

www.tuv.com
ID 9108636595



WEICON Solutions for
**Energy
Technology**

Art.-No. 10901102

Distributed by:

All specifications and recommendations in this brochure are not guaranteed properties. They are based on our research results and experience. However, they are non-binding because we cannot be responsible for compliance with the processing conditions as we are not aware of the user's special application conditions. We can only provide a guarantee for the consistently high quality of our products. We recommend that you carry out your own appropriate tests to determine whether the properties you require can be achieved with the specified product. No claims can be derived from the user bears the sole responsibility for non-appropriate or other than specified applications.
BU/10901102/10/18